333 Frankcom Str., Ajax, Ontario L1S 1R4 Tel.: (905) 426-3243 Fax: (905) 426-2160

www.safetystrap.com

TOLL FREE: 1-800-547-4298

(In Canada and the U.S.A.)

RESIDENTIAL CHOKER

WARNING!!!

- FAILURE TO READ AND UNDERSTAND THESE INSTALLATION PROCEDURES MAY RESULT IN SERIOUS INJURY OR DEATH.
- SYNTHETIC STRAPS SHOULD NOT BE USED IN EXCESS OF 200 DEGREES FAHRENHEIT/ AVOID DAMAGING FROM WELDING SPARKS AND CORROSIVE CHEMICALS
- CAREFULLY READ AND FOLLOW ALL INSTALLATION INSTRUCTIONS AND ALL SPECIFICATIONS FOR USE
 OF THIS PRODUCT.
- SAFE-T-STRAP IS A NON-REUSABLE FALL-ARREST SYSTEM AND WE ASSUME NO LIABILITY CONNECTED WITH ITS RE-USE
- THE USER IS REMINDED BEFORE A SAFE-T-STRAP IS ATTACHED TO ANY MEMBER ON A PRODUCT, THE MEMBER SHALL BE SO FRAMED FASTENED, TIED AND BRACED SO AS TO PROVIDE THE REQUIRED STRENGTH AND RIGIDITY.
- SAFE-T-STRAP MUST BE INSTALLED AS REQUIRED BY THE MANUFACTURE'S PROCEDURES UNDER THE SUPERVISION OF A COMPETENT PERSON TRAINED IN ITS PROPER INSTALLATION.
- THE SAFE-T-STRAP IS A COMPONENT OF A FALL-ARREST SYSTEM. LOCATION OF INDIVIDUAL STRAPS WILL VARY AND SPECIFIC PROCEDURES FOR INSTALLATION WILL BE REQUIRED TO ENSURE ADEQUATE FALL PROTECTION FOR WORKERS.

NOTE: AFTER CONSTRUCTION IS COMPLETE, ALL REMAINING EXPOSED SAFE-T-STRAPS SHOULD BE REMOVED.

INSTALLATION INSTRUCTIONS

- THE RESIDENTIAL CHOKER STRAP CONSISTS OF A FLAT LOOP AT EACH END OR A FLAT LOOP ON ONE END AND A D-RING ON THE OTHER. THE END WITH OPTIONAL D-RING HAS A LABEL SEWN IN AND THE OTHER IS JUST A LOOP.
- THE SMALLER LOOP IS CHOKED THROUGH THE LABELLED LOOP AROUND THE TOP PLATES OF THE WALL (FIGURE 1) OR TRUSS (FIGURE 2). A MINIMUM 3" NAIL IS THE HAMMERED THROUGH THE STITCHED AREA TO ENSURE ANCHOR IS FIRMMLY IN PLACE. IN THE CASE OF 2X4 TRUSS THE NAIL IS PLACED IN STITCHED AREA THROUGH THE 4" PORTION OF THE TOP CORD.
- IN A RETRO-FIT APPLICATION THE NAIL MAY BE OMITTED. THE RESIDENTIAL SAFE-T-STRAPS ARE DESIGNED FOR SINGLE USE ONLY. EACH STRAP MUST BE INSPECTED BY A COMPETENT WORKER BEFORE EACH USE.



